

TALON R/C

REMOTE CONTROL



MODELS:

2844VGE 28hp, 44" Deck




Talon R/C 2844VGE shown

MOW WHERE NO MOWER HAS MOWED BEFORE.

The **Talon R/C** is the safest and most productive solution for commercial and municipal operators who need to maintain steep hills, ditches, wet terrains, and areas zero-turn mowers struggle to perform.

- **Remote Control** - Keep operators safe in areas needing maintained with remote control technology with nearly 500 feet of range.
- **American Muscle** - Powered by a 28 horsepower Vanguard® EFI engine, the Talon R/C has plenty of power to cut, climb, and maneuver any terrain.
- **Hillside Ready** - Mow slopes up to 55 degrees in areas where operators should never be on the equipment.
- **Hybrid Technology** - Electric drive system for advanced operator controls and variable speed.
- **Low Ground Pressure** - Maximize your efficiency while minimizing your footprint.
- **Variable Cutting Height** - Choose your cutting height on the remote from just one 1" all the way to 6" to get the perfect cut at every job.



Safe for Slopes - Safely mow slopes up to 55 degrees with ease



EFI Engine - Improved fuel economy and easier cold starts



Hybrid Power - Electric drive system for smooth control



Mulching Deck - Twin spindle design for attractive finish in all grass types.



Bi-Directional Cutting - Improves efficiency by reducing turning

**1 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*1 year or 1,500 hour limited warranty, see dealer for complete details



TALON R/C



44" Deck

2844VGE

Model	
Engine	
Manufacturer	Vanguard® EFI and Oil Guard System
Horsepower	28
Displacement	810cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner
Cooling	Air-cooled
Starter	Electric
Fuel capacity	2 gallons
Maximum noise levels	98 db(A)
Engine warranty	3-Year

Drive System	
Drive motors	48V AC electric motor to final reduction
Ground speed	5 mph

Mower Deck	
Deck size	44"
Discharge	Rear
Cutting height	1" - 6"
Programmable low height setting	Standard
Bi-directional cutting	Standard
High Lift mulching blades	Standard
Deck Engagement	Ogura® 250 ft-lbs
Blade tip speed (approximate)	18,044 fpm
Fast-stop rotors	Standard (3 seconds)

Tracks	
Universal rubber	Standard
Maximum working angle	55 degrees in side to side mowing applications
Track length	39.4"

Remote Controls	
Working range	492 feet
Frequency	434 Mhz
Battery	2 rechargeable batteries
Proportional joysticks	Standard

Dimensions	
Overall height (deck at lowest height)	30.1"
Overall height (deck at highest height)	36"
Overall width	59"
Overall length (without attachment)	59.5"
Weight	1058 lbs