



Taking Science to the Sewer®!

Part Number ORN01-ORCA™ TIER III NOZZLE

- Low Carbon STAINLESS Steel Construction
- SBR Rubber Conduit Cover
- Twenty-four Inch OAL by 4.5" Diameter
- Fourteen Pounds with Swivel (Only 1 Swivel Required, Can Use 2)
- Zero to Three Thousand P.S.I. Working Pressure
- Ten Thousand P.S.I. Minimum Burst
- Four Rear Supply Jetting Conduits (One Truck)
- Four Rear Supply Jetting Conduits (2nd Truck)
- 0.0 mm – 6.0 mm Exchangeable Jets
- Four Hundred Gallon per Minute Capacity with maximum pressures at 4000 P.S.I.



Part Number ORN01 "ORCA™" TIER III NOZZLE

- Hose Size: Two separate hoses (any standard size) 1 Swivel is required/Can use 2
- Flow rates: 60 to 400 GPM
- Pipe Sizes: 15" and up
- Jet Sizes: 1.9mm to 6.0mm
- Sled Sizes: One nonadjustable
- Comments: Used primarily in 15" and up Sanitary and Storm Sewers. Continuous water supply suggested.

NozzTeq® Inc. 1497 Main St. Unit# 354, Dunedin, FL 34698
866-620-5915 FAX 603-413-6744
info@nozzteq.com www.nozzteq.com

Also Visit our online store at:
<http://www.cole-mart.com/nozzteq>